aspenstate



aspen XDR

Straight Arm Digital Radiography System

Aspenstate's Straight Arm DR is a complete universal system that offers an advanced digital x-ray solution in a design that is compact and efficient.

Aspen XDR features a 17 x 17 detector for superior image quality and allows for all imaging views that are required in radiology with maximum patient safety & flexibility.

The Aspen XDR maximizes every square foot of space in a small environment so as to allow the staff more room to maneuver.

Owing to its compact design, the AspenXDR is a low-cost radiography system which is space efficient and requires a short installation time.



The system is composed of a floor-to-wall column and a rotatable arm with variable height center

It is easy to operate and allows radiographic procedures to be completed in a quick and safe manner.

It allows exposures of patients in a standing, sitting or laying position.







X-ray & Mechanical		
Motorized Movement	1) Source to Image Distance (SID) control 2) Arm elevating movement at vertical	
Source to Image	100~180cm / 40~72 Inch (Continuously Adjustable)	
Vertical Travel	Max. 120cm / 47.2 Inch	
Arm Rotation Angle	-30° ~120°	
Tube Rotation	±90°	
Detector Rotation	±45°	
Power Requirement	120VAC or 200-240VAC, 50/60Hz, 1000VA	
Options	Manual Control and motorized with touchable display / Bucky enclosure	
Туре	Class I	

Detector		
Sensor Type	a-Si with PIN diode	
Scintillator	Gadox / Cs:Tl	Aggestate
Dimension	460 x 460 x 15 mm (ISO 4090 cassette size)	
Weight	Approx. 5kg	
Active Pixel Area	430.08 x 430.08	
Pixel Resolution	3072 x 3072	
Pixel Pitch	140 µm	
AD Converter	16 bits	
Maximum Dose	80 μGy	100
X-ray Generator Interface	Trigger Mode / Smart AED Mode	
Image Preview Time	Less than 3 sec.	Large active area
Image Cycle	10 sec.	High resolution image quality
Interface	Gigabit Ethernet (1000BASE-T)	Smart Exposure Detection (SED)
X-ray Voltage Range	40 - 150 kVp	 Increased strength, reduced
Operation Environment	15° ~ 35°C, 30 ~ 85% RH (non-condensing)	weight & slim design
Power	DC 12V, 2.5A	 High value at a low investment
Component	Control Box	

aspenstate

www.aspenstate.com

Head Office

801 North Jupiter Rd. Ste. 200, Plano, TX 75074, USA Tel. +1-214-257-0113 Fax +1-214-257-0116

E-mail: aspens@aspenstate.com